

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039908 A1

- (51) International Patent Classification⁷: **C09J 183/04**, E06B 3/62, C03C 27/10
- (21) International Application Number: PCT/GB2003/004467
- (22) International Filing Date: 15 October 2003 (15.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0225372.2 31 October 2002 (31.10.2002) GB
- (71) Applicant and
(72) Inventor: FOREMAN, Paul, David [GB/GB]; 57 Herbert Road, Rainham, Kent ME8 9DA (GB).
- (72) Inventor: ZAREBSKI, Andrew; c/o Primasil Silicones Limited, Kington Road, Weobley, Herefordshire HR4 8QU (GB).
- (74) Agents: TOLLETT, Ian et al.; Williams Powell, Morley House, 26-30 Holborn Viaduct, London EC1A 2BP (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: GLAZING JOINT



(57) Abstract: A composition for glazing joints comprises (a) a siloxane polymer having a molecular weight of from 300,000 to 700,000, (b) a siloxane polymer having a molecular weight of from 10,000 to 100,000 (the ratio of component A to component B being in the range of from 10 to 1, to 3 to 1) and a cross linking agent. The composition is preferably sufficiently cross-linked to have an effective surface tackiness. A glazing strip (10) shaped for receiving two or more sheets may be formed from the composition. An advantage of the composition is that it remains adhesive so that in use, this allows glass sheets to be repositioned and removed when dismantling a partition wall.